

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 33 N., R. 23 E., MDM, NEVADA

CHAINS

44.75

The  $\frac{1}{4}$  sec. cor. of sec. 34, monumented with the 1894 Gould granite stone, 20x10x8 ins., plainly mkd.  $\frac{1}{4}$  on the N. face, firmly set 15 ins. in a mound of earth. Fred L. Gould, U.S. Deputy Surveyor, remonumented, under Contract No. 206, the original corner established by George W. Garside, U.S. Deputy Surveyor, in 1873, under Contract No. 55. The 1894 Gould corner was found in 1910 by Winfred A. Pray, U.S. Deputy Surveyor, under Contract No. 265.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N R23E  
 $\frac{1}{4}$  S 34  
T33N

1974

bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

GENERAL DESCRIPTION

The land resurveyed in Township 33 North, Range 23 East, is nearly level and is about 4,000 ft. above sea level. The soil is sandy clay loam. Vegetation consists of sagebrush, greasewood, and bunchgrass.

Access is provided by trail roads, and the principal users of the area are cattlemen. No mining activity or mineral formations of any consequence were noted during the survey.