

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,
THROUGH RANGE 38 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,
THROUGH RANGE 38 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Conkling, Jr. and T. K. Stewart,
U. S. Deputy Surveyors,
in 1881.

The standard cor. of Tps. 26 N., Rs. 38 and 39 E., monumented with a wooden fence post, 6x8 ins., firmly set and exposed 5 ft. above ground in a fence, bearing E. and W., and in line with a fence to the N. This point is so near record position in relation to the well marked original corners on the E. bdy. and being locally recognized as the corner point is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T26N
R38E R39E
S 36 | S 31

1974

WEST, along the S. bdy. of sec. 36.

Over nearly level land, through budsage and shadscale; along fence.

- 9.77 Fence cor., from which fences bear E. and S.
- 10.50 Graded road, bears ENE. curving to E., and WSW. curving to W.; along N. side of graded road.
- 40.87 Point for the standard ¼ sec. cor. of sec. 36, determined longitudinally at proportionate distance and latitudinally in line with extension of fence to the E.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T26N R38E
¼ S 36

1974

deposit broken glass and set a steel fence post, 5½ ft. long, 22 ins. in the ground alongside the iron post.