

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,  
THROUGH R. 38 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">S C T26N R38E <u>S 31   S 32</u></p>
	<p style="text-align: center;">1974</p>
	<p>insert the iron pipe inside the iron post and reset the wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>N. 89° 48' W., along the S. bdy. of sec. 31.</p>
	<p>Over nearly level land, through budsage, shadscale and greasewood.</p>
9.48	<p>Local monument, an iron pipe, 1½ ins. diam., firmly set and exposed 5 ins. above ground, with plate mkd.</p>
	<p style="text-align: center;"><u>31</u> 6   5</p>
	<p style="text-align: center;">RLS 161 1970</p>
	<p>An unmarked wooden post, 4x4x20 ins., was found loosely set alongside the iron pipe.</p>
25.50	<p>Trail road, bears NE. and SW.</p>
39.72	<p>The standard ¼ sec. cor. of sec. 31, monumented with a wooden hub, 6 ins. long, firmly set flush at ground level, with a mound of stone, 3 ft. base, 2 ft. high, N. An unmarked wooden post, 2x2x48 ins. long, square on one side was found wired to a wooden post, 4x4x48 ins. long, loosely set alongside the hub. This is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C T26N R38E <u>¼ S 31</u></p>
	<p style="text-align: center;">1974</p>
	<p>bury the wooden hub and reset the 4 in. squared post with the unmarked wooden post wired to it and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>