

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,
THROUGH R. 38 E., MDM, NEVADA

CHAINS	<p>N. 89° 46' W., beginning new measurement.</p> <p>Over nearly level land, through budsage, shadscale and greasewood.</p> <p>40.00 The standard corner of Tps. 26 N., Rs. 37 and 38 E., monumented with a wooden post, 4x4x48 ins. long, plainly mkd. with 6 notches on the N., E., S. and W. edges and other illegible scribing and firmly set in a mound of stone, with a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S C T26N R37E R38E <u>S 36 S 31</u></p> <p style="text-align: center;">1974</p> <p>reset the original wooden post and steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>This corner was tied in by tellurometer traverse under Group No. 389 and shown on Protraction Diagram No. 283.</p>
	<p>DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of the Survey Executed by G. W. Conkling, Jr. and T. K. Stewart, U.S. Deputy Surveyors, in 1881.</p>
	<p>From the standard cor. of Tps. 26 N., Rs. 38 and 39 E.</p> <p>N. 0° 26' E., bet. secs. 31 and 36.</p> <p>Over nearly level land, through greasewood.</p> <p>0.60 Graded road, bears E. and W.</p> <p>39.76 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>