## DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 N., R. 38 E., MDM, NEVADA

**CHAINS** 40.29

The cor. of secs. 1, 6, 7 and 12, monumented with a lava stone,  $14 \times 10 \times 8$  ins., plainly mkd. with 5 grooves on S. face and 1 notch on N. edge and firmly set in a mound of stone. (Record wooden post).

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T26N R38E R39E S 1 S 6 S 12 S 7

1974

bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 02' W., bet. secs. 1 and 6.

Over gently rolling land, sloping generally S., through budsage, shadscale and greasewood.

40.44

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, monumented with a lava stone, 10x6x6 ins., plainly mkd.  $\frac{1}{4}$  on W. face, and firmly set in a mound of stone. (Record wooden post).

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T26N R38E R39E - 4 S 1|S 6

1974

bury the original cornerstone and set a steel fence post,  $5\frac{1}{2}$  ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

NORTH, beginning new measurement.

Over gently rolling land, sloping generally S., through budsage, shadscale and greasewood.