

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 38 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T26N
R37E R38E
| $\frac{1}{4}$
| S 6

1974

bury the original cornerstone alongside the iron post.

N. $0^{\circ} 15'$ W., beginning new measurement.

Over rolling land, through budsage, shadscale and greasewood.

40.36

The cor. of Tps. 26 and 27 N., Rs. 37 and 38 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of T. 27 N., R. 37 E., executed under Group No. 89, in 1922.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G.W. Conkling, Jr. and T. K. Stewart,
U.S. Deputy Surveyors,
in 1881.

The corners along this boundary were established as common corners but will now function as corners for T. 26 N., R. 38 E., only.

From the cor. of Tps. 26 N., Rs. 38 and 39 E.

N. $88^{\circ} 21'$ W., along the N. bdy. of sec. 1.

Over gently rolling land, sloping generally S., through budsage, shadscale and greasewood.

40.03

The $\frac{1}{4}$ sec. cor. of sec. 1, monumented with a limestone, 10x10x10 ins., plainly mkd. $\frac{1}{4}$ on N. face and firmly set in a mound of stone.

At the corner point