

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 38 E., MDM, NEVADA

CHAINS	
	<p>S. 88° 35' W., beginning new measurement.</p> <p>Over rolling land, through budsage, shadscale and greasewood.</p>
22.00	Ridge, bears N. and S.
40.20	The cor. of Tps. 26 and 27 N., Rs. 37 and 38 E.
<p>DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 26 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by E. L. Bridges, U. S. Deputy Surveyor, in 1882.</p>	
<p>From the standard corner of secs. 35 and 36, on the S. bdy. of the Tp.</p>	
<p>N. 0° 07' E., bet. secs. 35 and 36.</p>	
<p>Over nearly level land; along fence.</p>	
0.30	Graded road, bears E., 0.27 chs. dist. from which roads bears N. and E.
41.11	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, determined latitudinally at proportionate distance and longitudinally in a fence, bearing N. and S.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
<p>T26N R38E $\frac{1}{4}$ S 35 S 36 1974</p>	
<p>N. 0° 05' E., beginning new measurement.</p>	
<p>Over nearly level land; along fence.</p>	
39.70	Intersection of roads, bears E., 0.25 chs. dist., from which a graded road, bears N. and S. and a trail road, bears E.
40.00	Graded road, bears W. and E., 0.25 chs. dist., then S.
41.11	<p>The cor. of secs. 25, 26, 35 and 36, determined at fence cor., from which fences bear S. and W. This position is locally recognized as the corner and is accepted as the best available evidence of the position of the original corner.</p>