

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS					
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R26E</p> <table style="margin: auto;"> <tr> <td>S 31</td><td>S 32</td></tr> <tr> <td>S 6</td><td>S 5</td></tr> </table> <p>T19N</p> <p>1974</p> </div> <p>deposit the original cornerstone and reset the iron pipe alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	S 31	S 32	S 6	S 5
S 31	S 32				
S 6	S 5				
	<p>N. 89° 34' W., bet. secs. 6 and 31.</p> <p>Over nearly level land, covered with shadscale and greasewood.</p>				
3.40	Wash, 40 lks. wide, 2 ft. deep, drains NE.				
31.00	Bladed road, bears NNE. and SSW.				
40.04	<p>The ¼ sec. cor. of secs. 6 and 31, monumented with an iron pipe, 2 ins. diam., firmly set showing 12 ins. above ground. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R26E</p> <table style="margin: auto;"> <tr> <td>S 31</td><td></td></tr> <tr> <td>¼ S 6</td><td></td></tr> </table> <p>T19N</p> <p>1974</p> </div> <p>reset the iron pipe alongside the iron post.</p>	S 31		¼ S 6	
S 31					
¼ S 6					
	<p>N. 89° 36' W., beginning new measurement.</p>				
31.50	Wash, 30 lks. wide, 2 ft. deep, drains N.				
38.20	<p>The cor. of Tps. 19 and 20 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set showing 12 ins. above ground, with a mound of stone S., with brass cap mkd.</p>				