

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS	<p>N. 1° 06' W., bet. secs. 7 and 12.</p> <p>Over gently rolling land, covered with shadscale and greasewood.</p> <p>40.67 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a basalt stone, 14x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R26E R27E $\frac{1}{4}$ S 12 S 7 1974</p> </div> <p>deposit the original cornerstone alongside the iron post.</p>	
	<p>N. 0° 28' W., beginning new measurement.</p> <p>Enter mountainous land; asc. 260 ft. over S. slope.</p> <p>40.59 The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 18x12x6 ins., firmly set in a mound of stone, mkd. with 5 notches on S. face and 1 notch on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R26E R27E S 1 S 6 S 12 S 7 1973</p> </div> <p>deposit the original cornerstone alongside the iron post.</p>	
	<p>N. 0° 03' W., bet. secs. 1 and 6.</p> <p>Over mountainous land, covered with shadscale and greasewood; asc. 200 ft. over S. slope.</p> <p>20.00 Spur, slopes E.; desc. 280 ft. over N. slope.</p> <p>32.50 Draw, drains E.; asc. 150 ft. over SE. slope.</p> <p>40.33 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 30x12x12 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p>	