

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS		
30.00 40.82	<p>S. 89° 04' W., beginning new measurement.</p> <p>Descend 180 ft. over W. slope.</p> <p>Draw, drains S.; asc. 120 ft. over SE. slope.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p>	
41.39	<p>N. 0° 25' E., bet. secs. 2 and 3.</p> <p>Over rolling land, covered with shadscale and greasewood.</p> <p>Ascend 280 ft. over SE. slope.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 3, monumented with a basalt stone, 24x14x8 ins., firmly set in a mound of stone, mkd. <math>\frac{1}{4}</math> on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R26E <math>\frac{1}{4}</math> S 3   S 2 1974</p> <p>deposit the original cornerstone alongside the iron post.</p> <p>This corner is located on a spur sloping SW.</p>	
48.83	<p>N. 0° 43' E., beginning new measurement.</p> <p>Descend 180 ft. over NW. slope.</p> <p>Intersect the Fourth Standard Parallel North.</p> <p>Point for the closing corner of secs. 2 and 3.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R26E S 34 S 3   S 2 C C T20N R26E 1974</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the original closing corner of secs. 2 and 3, bears N. 0° 43' E., 1.42 chs. dist., monumented with a basalt stone, 16x14x6 ins., firmly set 8 ins. in the ground, mkd. with CC and 6 grooves on S. face, 2 grooves on E. face and 4 grooves on W. face.</p> <p>Mark the stone with the letters AM for amended monument and bury.</p>	