

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS	
	S. 89° 52' W., beginning new measurement.
40.30	The cor. of secs. 3, 4, 9 and 10.
	<p>N. 0° 58' E., bet. secs. 3 and 4.</p> <p>Over rolling land, covered with shadscale and greasewood.</p> <p>Ascend 160 ft. over SE. slope.</p>
30.00	Spur, slopes SSW.; along general W. slope.
40.54	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4, monumented with a basalt stone, 16x12x8 ins., firmly set 10 ins. in the ground, mkd. <math>\frac{1}{4}</math> on W. face, with a mound of stone W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R26E <math>\frac{1}{4}</math> S 4   S 3  1974</p> <p>deposit the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 37' E., beginning new measurement.</p> <p>Along broken W. slope.</p>
39.00	Ravine, drains W.
50.47	<p>The closing corner of secs. 3 and 4, monumented with a basalt stone, 16x16x8 ins., firmly set 10 ins. in the ground, mkd. with 3 grooves on E. and W. faces, and CC on S. face, with a mound of stone S.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R26E S 33 <hr style="width: 50%; margin: 0 auto;"/>S 4   S 3 C C T20N R26E  1974</p> <p>deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>