

437

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 1¼ ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	$\begin{array}{r} \text{T20N R26E} \\ \frac{1}{4} \text{ S 30} \\ \text{S 31} \end{array}$
	1974
	deposit the original cornerstone and reset the iron pipe alongside the iron post.
	<hr/> N. 89° 12' W., beginning new measurement.
8.50	Powerline, bears S. 41¼° E. and N. 41¼° W.
38.13	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set showing 12 ins. above ground, with a steel fence post, 6 ft. long alongside, with brass cap mkd.
	$\begin{array}{r} \text{T20N} \\ \text{R25E R26E} \\ \text{S 25 S 30} \\ \text{S 36 S 31} \end{array}$
	1931
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0° 05' W., bet. secs. 29 and 30.
	Over nearly level desert land, covered with shadscale and greasewood.
40.06	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T20N R26E} \\ \frac{1}{4} \\ \text{S 30 S 29} \end{array}$
	1974
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
64.10	Telephone line, bears S. 48° E. and N. 48° W.
72.30	U.S. Highway No. 95-A, bears S. 53° E. and N. 53° W.