

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS		
39.36	<p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T20N R26E \\ \frac{1}{4} \frac{S 18}{S 19} \\ 1974 \end{array}$ <p>set a wooden post, 4 ft. long, 4 ins. square, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	
77.39	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set showing 12 ins. above ground, with brass cap mkd.</p> $\begin{array}{r} T20N \\ R25E R26E \\ S 13 S 18 \\ S 24 S 19 \\ 1931 \end{array}$	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. $0^{\circ} 46'$ E., bet. secs. 17 and 18.</p> <p>Over nearly level land, covered with shadscale and greasewood.</p>	
39.80	Trail road, bears SSE. and NNW.	
40.73	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a basalt stone, 22x12x6 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T20N R26E \\ \frac{1}{4} \\ S 18 S 17 \\ 1974 \end{array}$ <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.</p>	
	N. $0^{\circ} 39'$ E., beginning new measurement.	
30.70	Powerline, bears N. $18\frac{1}{2}^{\circ}$ E. and S. $18\frac{1}{2}^{\circ}$ W.	
38.50	Trail road, bears NNE. and SSW.	
41.10	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a basalt stone, 20x12x6 ins., firmly set 15 ins. in the ground, mkd. with 4 notches on S. edge and 5 notches on E. edge.</p>	