

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N R26E} \\ \text{S } 7 \\ \hline \frac{1}{4} \text{ S } 18 \end{array}$$

1974

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.

N. 85° 06' W., beginning new measurement.

38.36 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set showing 12 ins. above ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N} \\ \text{R25E R26E} \\ \text{S } 12 \text{ | S } 7 \\ \hline \text{S } 13 \text{ | S } 18 \end{array}$$

1931

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 36' E., bet. secs. 7 and 8.

Over nearly level land, covered with shadscale and greasewood.

40.45 The ¼ sec. cor. of secs. 7 and 8, monumented with a basalt stone, 14x12x6 ins., firmly set 10 ins. in the ground, mkd. ¼ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N R26E} \\ \frac{1}{4} \\ \text{S } 7 \text{ | S } 8 \end{array}$$

1974

deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 38' E., beginning new measurement.

40.52 The cor. of secs. 5, 6, 7 and 8, monumented with a basalt stone, 18x8x8 ins., firmly set 12 ins. in the ground, mkd. with 5 notches on the S. and E. edges.