

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 26 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N R26E} \\ \text{S } 6 \\ \hline \frac{1}{4} \text{ S } 7 \end{array}$$

1974

deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.

N. 85° 01' W., beginning new measurement.

39.43 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N} \\ \text{R25E R26E} \\ \text{S } 1 \text{ | S } 6 \\ \hline \text{S } 12 \text{ | S } 7 \end{array}$$

1931

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 30' E., bet. secs. 5 and 6.

Over nearly level land, covered with shadscale and greasewood.

41.94 Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T20N R26E} \\ \frac{1}{4} \\ \text{S } 6 \text{ | S } 5 \end{array}$$

1974

set a steel fence post, 6 ft. long, alongside the iron post.

47.00 Enter marsh, edge bears NNE. and SSW., over marsh.

89.64 The closing corner of secs. 5 and 6, monumented with a basalt stone, 16x10x8 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on the E. edge, 1 notch on the W. edge and CC on S. face.

At the corner point