

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,  
THROUGH R. 26 E., MDM, NEVADA

CHAINS	<p>S C T21N R26E <u>S 31   S 32</u></p> <p>1974</p> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, 24 ins. in the ground, alongside the iron post.</p>	
<p>11.71</p>	<p>S. 89° 55' W., along the S. bdy. of sec. 31.</p> <p>Over sink.</p> <p>The closing corner of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a steel fence post alongside the iron post, with brass cap mkd. as described in the field notes of T. 20 N., R. 26 E., resurveyed concurrently under this same group.</p>	
<p>40.04</p>	<p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>S C T21N R26E <u>¼ S 31</u></p> <p>1974</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	
<p>51.27</p>	<p>The ¼ sec. cor. of sec. 6, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a steel fence post alongside the iron post, with brass cap mkd. as described in the field notes of T. 20 N., R. 26 E., resurveyed concurrently under this same group.</p>	
<p>78.37</p>	<p>The standard cor. of Tps. 21 N., Rs. 25 and 26 E., monumented with a basalt stone, 24x16x6 ins., firmly set 12 ins. in the ground, mkd. with 6 grooves on E., W. and N. faces.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	