

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R25E R26E $\frac{1}{4}$ S 12 S 7</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post.</p> <hr/> <p>N. $0^{\circ} 05'$ W., beginning new measurement.</p> <p>Over rolling land; asc. 40 ft. over S. slope.</p> <p>5.60 Powerline, bears N. $41\frac{1}{2}^{\circ}$ E. and S. $41\frac{1}{2}^{\circ}$ W.; asc. 40 ft. over S. slope.</p> <p>32.00 Top of ascent; desc. 30 ft. over NW. slope.</p> <p>39.90 The cor. of secs. 1, 6, 7 and 12, monumented with a volcanic stone, $24 \times 14 \times 10$ ins., firmly set 10 ins. in the ground, with 5 notches on S. edge and 1 groove on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R25E R26E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. $0^{\circ} 01'$ E., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with medium greasewood and shadscale; desc. 120 ft. over N. slope.</p> <p>26.80 Wash, 20 lks. wide, 6 ft. deep, drains E.; asc. 130 ft. over SE. slope changing to an E. slope.</p> <p>40.03 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a volcanic stone, $16 \times 10 \times 8$ ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W. of cor.</p> <p>At the corner point</p>