

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R26E S 23 S 24 S 26 S 25</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
40.09	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and extending 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 N., R. 27 E., resurveyed concurrently under this same group.</p> <p>N. 89° 45' W., bet. secs. 24 and 25.</p> <p>Over mountainous land, covered with medium greasewood and shadscale; asc. 110 ft. over E. slope.</p> <p>The ¼ sec. cor. of secs. 24 and 25, monumented with a basalt stone, 17x10x7 ins., firmly set 10 ins. in the ground, mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R26E ¼ S 24 S 25</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	
36.60	<p>N. 89° 46' W., beginning new measurement.</p> <p>Over mountainous land; asc. 550 ft. over E. slope.</p> <p>Ridge, bears N. and S.; desc. 40 ft. over NW. slope.</p>	
40.13	<p>The cor. of secs. 23, 24, 25 and 26.</p>	
40.03	<p>N. 0° 15' E., bet. secs. 23 and 24.</p> <p>Over mountainous land, covered with medium greasewood and shadscale; desc. 150 ft. over NW. slope.</p> <p>The ¼ sec. cor. of secs. 23 and 24, monumented with a basalt stone, 27x13x9 ins., firmly set in a mound of stone, mkd. ¼ on W. face.</p>	