

472

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

<p>CHAINS 39.96</p>	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a basalt stone, 26x18x12 ins., firmly set 9 ins. in the ground, mkd. with 4 grooves on S. face and 1 groove on E. face, with a mound of stone, W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;"> T21N R26E <u>S 11 S 12</u> S 14 S 13 </p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post.</p>
<p>2.50</p>	<p>S. 89° 57' E., bet. secs. 12 and 13.</p> <p>Over mountainous land, covered with medium greasewood and shadscale; asc. 20 ft. over NW. slope.</p>
<p>17.00</p>	<p>Ridge, bears NE. and SW.; desc. 190 ft. over E. slope.</p>
<p>39.95</p>	<p>The ¼ sec. cor. of secs. 12 and 13, monumented with a basalt stone, 18x9x6 ins., firmly set 6 ins. in the ground, mkd. ¼ on N. face, with a mound of stone N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;"> T21N R26E ¼ <u>S 12</u> S 13 </p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post.</p>
<p>40.19</p>	<p>S. 89° 55' E., beginning new measurement.</p> <p>Over mountainous land; asc. 160 ft. over W. slope.</p> <p>Intersect the W. bdy. of sec. 7, T. 21 N., R. 27 E.</p> <p>The closing corner of secs. 12 and 13, monumented with a basalt stone, 15x15x8 ins., firmly set in a mound of stone, mkd. with 4 grooves on S. face, 2 grooves on N. face and CC on W. face.</p>