

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS														
<p>11.30</p> <p>40.31</p>	<p>S. 89° 52' E., beginning new measurement.</p> <p>Over mountainous land; desc. 140 ft. over NE. slope.</p> <p>Draw, drains NE.; asc. 160 ft. over broken NW. slope.</p> <p>Intersect the W. bdy. of sec. 6, T. 21 N., R. 26 E.</p> <p>The closing corner of secs. 1 and 12, monumented with a basalt stone, 22x10x8 ins., firmly set 10 ins. in the ground, mkd. with 5 grooves on S. face, 1 groove on N. face and CC on W. face, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T21N</td><td> </td><td>T21N</td></tr> <tr><td>R26E</td><td> </td><td>R27E</td></tr> <tr><td>C S 1</td><td> </td><td>S 6</td></tr> <tr><td>C S 12</td><td> </td><td></td></tr> </table> <p>1974</p> </div> <p>deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the cor. of secs. 6 and 7, T. 21 N., R. 27 E., bears S. 0° 02' E., 5.50 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 21 N., R. 27 E., resurveyed concurrently under this same group.</p>	T21N		T21N	R26E		R27E	C S 1		S 6	C S 12			
T21N		T21N												
R26E		R27E												
C S 1		S 6												
C S 12														
	<p>The point for the E. ¼ sec. cor. of sec. 12, is at mid-point and on the E. bdy. of the Tp.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T21N</td><td> </td><td></td></tr> <tr><td>R26E</td><td> </td><td></td></tr> <tr><td>¼</td><td> </td><td></td></tr> <tr><td>S 12</td><td> </td><td></td></tr> </table> <p>1974</p> </div> <p>From this corner, the ¼ sec. cor. of sec. 7, T. 21 N., R. 27 E., bears S. 0° 01' W., 5.81 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 21 N., R. 27 E., resurveyed concurrently under this same group.</p>	T21N			R26E			¼			S 12			
T21N														
R26E														
¼														
S 12														