

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS

The point for the E.  $\frac{1}{4}$  sec. cor. of sec. 1, is at proportionate distance and on the E. bdy. of the Tp.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N |  
R26E |  
 $\frac{1}{4}$  |  
S 1 |

1974

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, the  $\frac{1}{4}$  sec. cor. of sec. 6, T. 21 N., R. 27 E., bears S.  $0^{\circ} 05'$  E., 5.26 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and extending 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 21 N., R. 27 E., resurveyed concurrently under this same group.

From the cor. of secs. 1, 2, 11 and 12.

NORTH, bet. secs. 1 and 2.

Over rolling land, covered with medium greasewood and shadscale; desc. 90 ft. over NW. slope changing to a N. slope.

40.01 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 2, monumented with a basalt stone, 25x9x6 ins., firmly set 6 ins. in the ground, mkd.  $\frac{1}{4}$  on W. face, with mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T21N R26E  
 $\frac{1}{4}$   
S 2 | S 1

1974

deposit the original cornerstone alongside the iron post.

N.  $0^{\circ} 08'$  W., beginning new measurement.

Over rolling land; desc. 180 ft. over N. slope.

34.42 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, W. of cor., with brass cap mkd. as described in the field notes of T. 22 N., R. 26 E., resurveyed concurrently under this same group.