

484

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS		
	<p style="text-align: center;">T21N R26E $\frac{1}{4}$ $\frac{S \ 2}{S \ 11}$ 1974</p> <p>deposit the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>WEST, beginning new measurement.</p> <p>Over rolling land; asc. 80 ft. over NE. slope changing to a N. slope.</p> <p>23.00 Spur, slopes NNE.; desc. 80 ft. ^{over} / broken NW. slope.</p> <p>40.08 The cor. of secs. 2, 3, 10 and 11.</p>	
	<p>N. 0° 11' W., bet. secs. 2 and 3.</p> <p>Over rolling land, covered with medium greasewood and shadscale; desc. 80 ft.</p> <p>40.02 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a basalt stone, 15x9x5 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R26E $\frac{1}{4}$ $S \ 3 S \ 2$ 1974</p> <p>deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 19' W., beginning new measurement.</p> <p>Over rolling land; desc. 30 ft. over NW. slope.</p> <p>34.44 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of T. 22 N., R. 26 E., resurveyed concurrently under this same group.</p>	