

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T21N R26E

$\frac{1}{4}$
S 4 | S 3

1974

deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 4 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 08'$ W., beginning new measurement.

Over a sink.

11.30 Underground telephone line, bears N. $59\frac{1}{2}^{\circ}$ E. and S. $59\frac{1}{2}^{\circ}$ W.

34.02 Intersect the S. bdy. of sec. 34, T. 22 N., R. 26 E.

The closing corner of secs. 3 and 4, monumented with a basalt stone, $14 \times 8 \times 4$ ins., firmly set 8 ins. in the ground, mkd. with CC on top and 3 notches on E. and W. edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T22N R26E

S 34

S 4 | S 3

CC

T21N R26E

1974

deposit the original cornerstone and set a wooden post, 4×4 ins. square, 5 ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, the cor. of secs. 33 and 34, T. 22 N., R. 26 E., bears S. $89^{\circ} 59'$ W., 0.74 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, extending 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 22 N., R. 26 E., resurveyed concurrently under this same group.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, is at mid-point and on the N. bdy. of the Tp.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.