

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS	
	<p>N. 0° 02' W., bet. secs. 4 and 5.</p> <p>Over a sink.</p>
4.30	<p>Underground telephone line, bears N. 59½° E. and S. 59½° W.</p>
39.50	<p>Seep spring.</p>
40.00	<p>The ¼ sec. cor. of secs. 4 and 5, monumented with a basalt stone, 14x6x6 ins., firmly set 8 ins. in the ground, mkd. ¼ on W. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R26E ¼ S 5 S 4</p>
	<p style="text-align: center;">1974</p>
	<p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 04' E., beginning new measurement.</p>
	<p>Over a sink.</p>
33.01	<p>Intersect Interstate 80 right-of-way, bears N. 39° 59' E., and S. 39° 59' W.</p>
33.82	<p>Intersect the S. bdy. of sec. 33, T. 22 N., R. 26 E.</p>
	<p>The closing corner of secs. 4 and 5, monumented with a basalt stone, 14x10x10 ins., firmly set in a mound of stone, mkd. with 4 grooves on E. face, 2 grooves on W. face and CC on top.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T22N R26E S 33 S 5 S 4 C C T21N R26E</p>
	<p style="text-align: center;">1974</p>
	<p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
	<p>From this corner, the cor. of secs. 32 and 33, T. 22 N., R. 26 E., bears N. 89° 58' W., 1.19 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set extending 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 22 N., R. 26 E., resurveyed concurrently under this same group.</p>