

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 21 N., R. 26 E., MDM, NEVADA

CHAINS	
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 10' W., bet. secs. 5 and 6.
	Over a sink.
13.00	Leave sink; enter gently rolling land, covered with medium greasewood and shadscale, edge bears NE. and SSW.
29.40	Telephone line, bears N. 39½° E. and S. 39½° W.
39.98	The ¼ sec. cor. of secs. 5 and 6, monumented with a ¾ in. rebar, 16 ins. long, firmly set 6 ins. in the ground and in a mound of stone. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T21N R26E
	¼
	S 6   S 5
	1974
	deposit the rebar alongside the iron post.
	N. 0° 12' E., beginning new measurement.
	Over gently rolling land; asc. 90 ft. over SE. slope.
28.60	Powerline, bears N. 37¼° E. and S. 37¼° W.
33.83	Intersect the S. bdy. of sec. 32, T. 22 N., R. 26 E.
	The closing corner of secs. 5 and 6, monumented with a basalt stone, 16x8x8 ins., firmly set in a mound of stone, mkd. with CC on top, 5 grooves on E. face and 1 groove on W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T22N R26E
	S 32
	S 6   S 5
	C C
	T21N R26E
	1974
	deposit the original cornerstone alongside the iron post.