TOWNSHIP 22 NORTH, RANGE 26 EAST, MDM, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the boundaries and the subdivisional lines of Township 22 North, Range 26 East, Mount Diablo Meridian, Nevada.

The east boundary was surveyed in 1868 by E. B. Monroe, U.S. Deputy Surveyor, under Contract 19. The south, west, and north boundaries and the subdivisional lines were surveyed and the east boundary resurveyed by F. A. Criss, U.S. Deputy Surveyor, in 1901 under Contract 224. The south boundary was resurveyed in 1905 by J. B. Menardi, U.S. Deputy Surveyor, under Contract 244. W. H. Craigue, Associate Transitman, and W. O. Secor, U. S. Transitman, retraced the north and east boundaries in 1911, under Group No. 13, Nevada.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the special instructions dated July 29, 1974.

The directions of the lines of this survey were determined by sustained angulation to and through the survey from U.S.C. & G.S. triangulation station "AGIE."

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate measurement, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of the township as determined from a tie made to U.S.C. & G.S. triangulation station "AGIE," located in sec. 28, is at latitude 39° 43' 22" N. and longitude 119° 00' 04" W., as calculated along section lines.

The mean magnetic declination is $17\frac{10}{2}$ east.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 22 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by F. H. Criss, U.S. Deputy Surveyor, in 1901, and the Resurvey Executed by J. B. Menardi, U.S. Deputy Surveyor, in 1905.

Beginning at the cor. of Tps. 21 and 22 N., Rs. 26 and 27 E., monumented with a lava stone, 20x12x12 ins., mkd. with 6 notches on all four edges, and mkd. T. 22 N., on N. face and T. 21 N., on S. face, firmly set and exposed 10 ins. above ground.