

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 22 N., R. 26 E., MDM, NEVADA

CHAINS		
	<p>from which</p> <p>U.S.C. & G.S. triangulation station "SEEP," bears S. 2° 50' W., 31.58 chs. dist., monumented with a standard brass cap, 3½ ins. diam., firmly cemented into a drill hole in a large rock, with top mkd. SEEP 1958, and a triangle.</p> <hr/> <p>N. 89° 59' W., beginning new measurement.</p> <p>Over nearly level land.</p>	
1.90	Telephone line, bears N. 39½° E. and S. 39½° W.	
34.90	Powerline, bears N. 37¼° E. and S. 37¼° W.	
38.63	The closing corner of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., firmly set and exposed 22 ins. above ground and in a mound of stone, 5 ft. base, mkd. as described in the field notes of the resurvey of T. 21 N., R. 26 E., surveyed concurrently under this same group.	
40.12	<p>The cor. of secs. 31 and 32, monumented with a lava stone, 24x10x8 ins., firmly set in a mound of stone, 2½ ft. base, with no discernible markings.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R26E</p> <p>S 31 S 32</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 6</p> <p>T21N</p> <p>1974</p> </div> <p>deposit the original cornerstone alongside the iron post.</p>	
	<p>WEST, along the S. bdy. of sec. 31.</p> <p>Ascend 130 ft. over broken rocky NE. slope, changing to a SE. slope, through scatterings of cheatgrass.</p>	
38.63	The ¼ sec. cor. of sec. 6, monumented with an iron post, 2½ ins. diam., firmly set and exposed 18 ins. above ground, and in a mound of stone, 4 ft. base, mkd. as described in the field notes of the resurvey of T. 21 N., R. 26 E., surveyed concurrently under this same group.	
40.39	The ¼ sec. cor. of sec. 31, monumented with a lava stone, 16x14x10 ins., mkd. ¼ on N. face, firmly set in a mound of stone, 3 ft. base.	