DEPENDENT RESURVEY OF THE WEST BOUNDARY,

<u>T. 22 N., R. 26 E., MDM, NEVADA</u> CHAINS Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd. T22N R25E R26E S 1 S 6 S 12 S 7 1974 deposit the original cornerstone alongside the iron post.

N. 0° 03' E., bet. secs. 1 and 6.

Ascend 200 ft. over broken rocky SE. slope, through scatterings of cheatgrass.

40.21 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a lava stone, 18x12x10 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone, 3 ft. base.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

> T22N R25E R26E s 1|s 6

> > 1974

deposit original cornerstone alongside the iron post.

N. 0° 02' W., beginning new measurement.

Ascend 130 ft. over broken rocky SE. slope.

39.84 The cor. of Tps. 22 and 23 N., Rs. 25 and 26 E., monumented with a lava stone, 30x24x16 ins., mkd. with 6 grooves on all 4 faces and T22N R25 & R26E on S. face, and T23N R25 & R26E on N. face, firmly set in a mound of stone, 3 ft. base.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

> T23N R25E R26E <u>s 36|s 31</u> 1 S T22N

> > 1974

deposit the original cornerstone alongside the iron post.