DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 20 N., R. 27 E., MDM, NEVADA CHAINS N. 0° 02' W., bet. secs. 1 and 6. Over nearly level land, through shadscale and greasewood. The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, monumented with a wooden post, 3 ins. square, 24 ins. long, mkd.  $\frac{1}{4}$ S on 41.10 W. face, firmly set and exposed 4 ins. above ground. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. MOST R27E R28E s 11s 6 1974 deposit the original wooden post alongside the iron post and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. N. 0° 01' W., beginning new measurement. Over nearly level land. 48.28 The closing corner of Tps. 20 N., Rs. 27 and 28 E., monumented with a lava stone, 12x10x10 ins., mkd. with 6 grooves on E., S., and W. faces, and CC on top. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T21N R27E S 36 S 1 S 6 R27E R28E T20N C1974 deposit the original cornerstone alongside the iron post. From this corner, the standard cor. of Tps. 21 N., Rs. 27 and 28 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 8 ins. above ground, mkd. as described in the field notes of the resurvey of the Fourth Standard Parallel North, through Range 27 East, executed concurrently under this same Group, bears N. 89° 02' E., 17.27 chs. dist.