DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 20 N., R. 27 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 20 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by H. H. Bence, U. S. Deputy Surveyor, in 1887.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 0° 01' W., bet. secs. 35 and 36.

Over nearly level land, through shadscale and greasewood.

40.38

The 4 sec. cor. of secs. 35 and 36, monumented with a lava stone, 8x6x5 ins., mkd. 4 on W. face, firmly set and exposed 4 ins. above ground, alongside of which is a wooden post, 3 ins. square, 24 ins. long, with illegible scribe marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.

T20N R27E ¼ S 35 |S 36

1974

deposit the original cornerstone and the wooden post alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. 0° 01' W., beginning new measurement.

Over nearly level land.

40.50

The cor. of secs. 25, 26, 35 and 36, monumented with a lava stone, 10x8x6 ins., mkd. with 5 notches on N. edge and 1 notch on S. edge, firmly set and exposed 6 ins. above ground, alongside of which is an iron pipe, 3/4 in. diam., firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.

T20N R27E S 26 S 25 S 35 S 36

1974

deposit the original cornerstone and iron pipe alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.