

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 27 E., MDM, NEVADA

CHAINS	
	N. 0° 08' W., beginning new measurement.
10.00	Enter intermingling of marshland and sandy hills, no definite edges.
47.40	Point for the closing corner of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner, falls in water, where corner cannot be perpetuated.
	From this point, the standard cor. of secs. 34 and 35, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, mkd. as described in the field notes of the resurvey of the Fourth Standard Parallel North, through R. 27 E., executed concurrently under this same group, bears N. 89° 58' E., 16.62 chs. dist.
	From this same point, the point selected for the witness closing corner of secs. 2 and 3, bears S. 89° 58' W., 4.00 chs. dist.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> W C T21N R27E S 34 S 3 S 2 → T20N R27E C C </div>
	1974
	set a steel fence post, 6 ft. long, alongside the iron post.
	The point for the ¼ sec. cor. of sec. 2 only, at midpoint on the N. bdy. of sec. 2.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> ¼ S 2 T20N R27E </div>
	1974
	set a steel fence post alongside the iron post.
	From this corner, the standard ¼ sec. cor. of sec. 35, monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, mkd. as described in the field notes of the resurvey of the Fourth Standard Parallel North, through R. 27 E., executed concurrently under this same group, bears N. 89° 58' E., 16.85 chs. dist.