

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 27 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N R27E

$\frac{1}{4}$
S 4 | S 3

1974

deposit the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

NORTH, beginning new measurement.

Over nearly level land; slong E. side of fence, converging to closing corner.

46.15

The closing corner of secs. 3 and 4, monumented with a lava stone, 18x14x10 ins., mkd. with 3 notches on E. and W. edges and CC on S. face, firmly set and exposed 12 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R27E

S 33
S 4 | S 3
T20N | R27E
C C

1974

deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Cor. located in a fence, extending N. 85° E. and S.

From this corner, the standard cor. of secs. 33 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, mkd. as described in the field notes of the resurvey of the Fourth Standard Parallel North, through R. 27 E., executed concurrently under this same group, bears S. $89^{\circ} 55'$ E., 16.05 chs. dist.

The point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, at midpoint on the N. bdy. of sec. 3, at this point a lava stone, 12x10x8 ins., mkd. $\frac{1}{4}$ on S. face, firmly set in a mound of stone, 3 ft. base.

At the corner point