

643

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 27 E., MDM, NEVADA

| CHAINS | |
|--------|--|
| | <p>N. 1° 27' E., bet. secs. 4 and 5.</p> <p>Ascend 20 ft. over SE. slope, through shadscale and greasewood.</p> |
| 40.04 | <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a lava stone, 14x12x12 ins., mkd. $\frac{1}{4}$ on W. face, firmly set and exposed 10 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 1° 10' W., beginning new measurement.</p> <p>Ascend 70 ft. over SE. slope.</p> |
| 0.10 | Dirt road, 10 lks. wide, bears ENE. and WSW. |
| 41.30 | Power line, bears N. 35° E. and S. 35° W. |
| 41.40 | Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W. |
| 46.20 | Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W. |
| 46.44 | <p>The closing cor. of secs. 4 and 5, monumented with a lava stone, 18x12x10 ins., mkd. with 6 grooves and CC on S. face and 4 grooves on E. face and 2 grooves on W. face, firmly set and exposed 5 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E S 32 S 5 S 4 T20N R27E C C</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> |