

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 20 N., R. 27 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R27E <math>\frac{1}{4}</math> S 6   S 5  1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p> <hr/> <p>N. <math>0^{\circ} 11'</math> E., beginning new measurement.</p> <p>Ascend 70 ft. over gentle SE. slope.</p> <p>46.58 The closing cor. of secs. 5 and 6, monumented with a lava stone, <math>14 \times 14 \times 8</math> ins., mkd. with 6 grooves and CC on S. face and 5 grooves on E. face and 1 groove on W. face, firmly set and exposed 1 in. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E S 31 <hr/>S 6   S 5 T20N   R27E C C  1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this corner, the standard cor. of secs. 31 and 32, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., exposed 4 ins. above ground, mkd. as described in the field notes of the resurvey of the Fourth Standard Parallel North, through R. 27 E., executed concurrently under this same group, bears N. <math>89^{\circ} 57'</math> E., 15.28 chs. dist.</p> <hr/> <p>The point for the <math>\frac{1}{4}</math> sec. cor. . of sec. 5 only, at midpoint on the N. bdy. of sec. 5, at this point a lava stone, <math>18 \times 14 \times 10</math> ins., mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of stone, 3 ft. base.</p> <p>At the corner point</p>	