

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,  
THROUGH R. 27 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
William Epler, U.S. Deputy Surveyor, in 1865,  
and the Resurvey of the East half of S. Bdy. of Sec. 33,  
and the S. Bdy. of Sec. 35, Executed by  
H.H. Bence, U.S. Deputy Surveyor, in 1887.

The standard Tp. cor. of Tps. 21 N., Rs. 27 and 28 E.,  
at proportionate distance; there is no remaining evidence  
of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins.  
in the ground, with brass cap mkd.

S C  
T21N  
R27E | R28E  
S 36 | S 31

1974

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this corner, the standard  $\frac{1}{4}$  sec. cor. of  
sec. 31, T. 21 N., R. 28 E., bears N.  $89^{\circ} 02' E.$ ,  
40.05 chs. dist., monumented with a squared willow  
post, 36 ins. long, 2 ins. square, mkd. with  
illegible scribing, loosely set 3 ins. in the  
ground.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  
22 ins. in the ground, with brass cap mkd.

S C  
T21N R28E  
 $\frac{1}{4}$  S 31

1974

reset the original wooden post alongside the iron  
post.

From this same corner, U.S.C. & G.S. triangulation  
station "UPSAL," bears S.  $81^{\circ} 20' E.$ , 398.16 chs.  
dist., monumented with a standard brass tablet,  
firmly set conforming to the record.

S.  $89^{\circ} 02' W.$ , on the S. bdy. of sec. 36.

Over nearly level land, covered with greasewood and  
shadscale.

17.27

The closing cor. of Tps. 20 N., Rs. 27 and 28 E., monu-  
mented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set  
showing 6 ins. above ground, with brass cap mkd. and  
witnessed as described in the field notes of T. 20 N.,  
R. 27 E., resurveyed concurrently under this same group.