DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 21 N., R. 27 E., MDM, NEVADA

CHAINS	N. 0° 21' W., bet. secs. 7 and 12.
`	Over nearly level desert land, covered with shadscale and greasewood.
40.29	The ¼ sec. cor. of secs. 7 and 12, monumented with a basalt stone, 14x8x6 ins., firmly set 10 ins. in the ground, mkd. ¼ on W. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.
	T21N R27E R28E 1/2
	S 12 S 7
	1974
	deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 17' W., beginning new measurement.
7.00	Trail road, bears ESE. and WNW.
40.36	The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 16x8x8 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on S. edge and 1 notch on N. edge.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.
	T21N R27E R28E S 1 S 6 S 12 S 7
	1974
	deposit the original cornerstone and set a wooden post, 4 ft. long, 2 ins. square, alongside the iron post.
,	N. 0° 32' W., bet. secs. 1 and 6.
	Over nearly level desert land, covered with shadscale and greasewood.
41.91	The 4 sec. cor. of secs. 1 and 6, monumented with a basalt stone, 8x8x8 ins., firmly set in a mound of earth, mkd. 4 on W. face.