

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 27 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E $\frac{1}{4}$ S 3 S 2</p> <p style="text-align: center;">1974</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <hr/> <p>N. $1^{\circ} 33'$ E., beginning new measurement.</p> <p>34.70 Trail road, bears E. and W.</p> <p>37.84 The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T22N R27E S 34 S 35 S 3 S 2 T21N</p> <p style="text-align: center;">1911</p>
	<p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.</p> <p>N. $2^{\circ} 23'$ W., bet. secs. 33 and 34.</p> <p>Over nearly level desert land, covered with shadscale and greasewood.</p> <p>1.30 Fence, bears N. $84\frac{1}{2}^{\circ}$ E. and S. $84\frac{1}{2}^{\circ}$ W.</p> <p>22.20 Trail road, bears ESE. and WNW.</p> <p>37.57 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a basalt stone, 12x10x8 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R27E $\frac{1}{4}$ S 33 S 34</p> <p style="text-align: center;">1974</p> <p>deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>