

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 41 N., R. 43 E., MDM, NEVADA

| CHAINS | |
|--------|---|
| | <p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., monumented with the original basalt stone, 16x14x10 ins., exposed 10 ins. above ground, plainly mkd. with 4 notches on S. edge and 2 notches on N. edge and firmly set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R43E R44E S 12 S 21 S 13 </p> <p style="text-align: center;">1975</p> <p>bury the cornerstone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>N. 1° 22' W., along the E. bdy. of sec. 12.</p> <p>Over mountainous land, through scattered sagebrush; desc. 170 ft. over N. slope to ¼ sec. cor.</p> |
| 16.20 | Trail road, bears NW. and SE. |
| 39.63 | <p>Point for the ¼ sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R43E R44E ¼ S 12 </p> <p style="text-align: center;">1975</p> <p>set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Descend 350 ft. over N. slope.</p> |
| 79.26 | <p>The cor. of secs. 1 and 12, monumented with the original basalt stone, 20x10x6 ins., exposed 12 ins. above ground, plainly mkd. with 5 grooves on S. face and 1 groove on N. face and firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, ½ ft. base, with brass cap mkd.</p> |