

DEPENDENT RESURVEY OF THE EAST BOUNDARY
T. 37 N., R. 56 E., MDM, NEVADA

CHAINS	
	N. 0° 18' E., bet. secs. 1 and 6.
	Over rolling land, covered with sagebrush.
39.97	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a granite stone, 16x12x6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with a steel fence post, 6 ft. long, showing $4\frac{1}{2}$ ft. above ground, set alongside.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T37N R56E R57E $\frac{1}{4}$ S 1 S 6 1975</p>
	deposit the original cornerstone and reset the steel fence post alongside the iron post.
	N. 2° 45' W., beginning new measurement.
	Over rolling land.
32.00	Draw, drains E.
41.28	The cor. of Tps. 37 and 38 N., Rs. 56 and 57 E., monumented with the decayed remains of a willow post, loosely set in a mound of earth, no scribe marks visible, with a quartzite stone, 15x12x10 ins., firmly set 9 ins. in the ground, mkd. with 6 notches on N., S., E. and W. edges, set alongside.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T38N R56E R57E <u>S 36 S 31</u> S 1 S 6 T37N 1975</p>
	deposit the original wooden post and the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.