

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF R. 57 E., MDM, NEVADA

## CHAINS

Point for the standard cor. of Tps. 36 N., Rs. 57 and 58 E., at proportionate distance; falls in the westbound lane of Interstate 80, bearing N.  $78^{\circ}$  E. and S.  $78^{\circ}$  W.; there is no remaining evidence of the original corner.

Set a copper-coated steel stake, 16 ins. long,  $\frac{1}{2}$  in. diam., 3 ins. below the surface, with top mkd.

S C  
S 36 | S 31

1975

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground, with a steel fence post alongside for a reference monument, bears SOUTH, 100 lks. dist., with brass cap mkd. RM 1975 and an arrow pointing to the corner.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 22 ins. in the ground, for a reference monument, bears NORTH, 300 lks. dist., with brass cap mkd. SC T36N R57E S36 RM 1975 and an arrow pointing to the corner.

From this cor., the standard  $\frac{1}{4}$  sec. cor. of sec. 31, T. 36 N., R. 58 E., monumented with the remains of a willow post, loosely set in a mound of earth, bears S.  $89^{\circ}$   $34'$  E., 40.28 chs. dist.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

S C  
T36N R58E  
 $\frac{1}{4}$  S 31

1975

reset the remains of the original wooden post and set a steel fence post,  $5\frac{1}{2}$  ft. long, 22 ins. in the ground, alongside the iron post.

from this corner

U.S.C. & G.S. triangulation station "JUDY," monumented with a standard bronze disk stamped JUDY 1957, firmly set in the top of a 10 in. circular concrete post, exposed 3 ins. above ground, bears N.  $47^{\circ}$   $34'$  E., 7.44 chs. dist.

N.  $89^{\circ}$   $34'$  W., along the S. bdy. of sec. 36.

Over gently rolling land, covered with sagebrush.