DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF R. 57 E., MDM, NEVADA Along a bladed strip. The standard cor. of secs. 31 and 32, monumented with an iron post, 3 ins. diam., firmly set and exposed 12 ins. above ground in a bladed strip, bearing N., E. and W., 80.88 with brass cap mkd. as described in the official record of T. 36 N., R. 57 E., executed under Group No. 28, in 1915. DEPENDENT RESURVEY OF THE EAST BOUNDARY. T. 36 N., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by Charles C. Tracy, U.S. Deputy Surveyor, in 1869. From the standard cor. of Tps. 36 N., Rs. 57 and 58 E. N. 0° 24' E., bet. secs. 31 and 36. Over gently rolling land, covered with sagebrush. 3.00 Intersect Interstate 80 right-of-way, fence bears N. 78° E. and S. 78° W. 10.50 Telephone cable, underground, bears N. 74 3/4° E. and S. 74 3/4° W. 40.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T36N R57E R58E S 36 S 31 1975 set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post. The cor. of secs. 25, 30, 31 and 36, monumented with the remains of a willow post, 1xl ins., 8 ins. long, loosely 80.80 set in a mound of earth, alongside a steel fence post, firmly set and exposed 3½ ft. above ground. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T36N R57E R58E S 25 S 30 S 36 S 31 1975 reset the remains of the original wooden post and steel fence post alongside the iron post.