

DEPENDENT RESURVEY OF THE EAST BOUNDARY  
T. 37 N., R. 57 E., MDM, NEVADA

CHAINS		
39.96	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a quartzite stone, 17x8x5 ins., mkd. with 5 grooves on the S. face and 1 groove on the N. face, firmly set and exposed 8 ins. above the ground, with a mound of stone to the W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R57E R58E S 1   S 6 S 12   S 7</p> <p style="text-align: center;">1977</p> <p>bury the original cornerstone and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</p>	
	<p>N. 0° 45' W., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with sagebrush; over a W. slope.</p>	
1.50	Ridge, bears E. and W.; desc. 140 ft. over a W. slope.	
23.50	Ravine, drains WSW.; over a W. slope.	
39.82	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a quartzite stone, 20x7x5 ins., mkd. ¼ on the W. face, firmly set and exposed 9 ins. above the ground, with a mound of stone to the W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T37N R57E R58E ¼ S 1   S 6</p> <p style="text-align: center;">1977</p> <p>bury the original cornerstone and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
	<p>N. 0° 27' E., beginning new measurement.</p> <p>Over rolling land; desc. 60 ft. over a W. slope.</p>	
9.50	Ravine, drains W.; desc. 20 ft. over a W. slope.	
17.50	Ravine, drains NW.; desc. 20 ft. over a W. slope.	