

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 62 E., MDM, NEVADA

CHAINS	
	from which
	A spring, 20 ft. in diam., bears N. 69° 54' E., 8.14 chs. dist.
	A spring, 10 ft. in diam., bears N. 73° 41' E., 6.75 chs. dist.
78.79	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 16 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 33 N., R. 61 E., surveyed under Group No. 56, alongside of which is a steel fence post, firmly set and exposed 4 ft.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 22' E., bet. secs. 5 and 6.
	Over nearly level land, through greasewood and grasses.
0.90	Fence, bears E. and W.
40.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T33N R62E $\frac{1}{4}$ S 6$\frac{1}{2}$S 5</p>
	1975
	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
81.22	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 14 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 34 N., R. 62 E., surveyed under Group No. 319, alongside of which is a steel fence post, firmly set and exposed 4 ft. above ground.
	GENERAL DESCRIPTION
	The area resurveyed within Township 33 North, Range 62 East is nearly level. The soil varies from a clay loam in the west and south, to a sandy alkali clay in the northeast. The vegetation consists of greasewood, shadscale, sagebrush and grasses.
	U.S. Highway No. 93 crosses the SW. corner of the Tp. There are several springs situated in section 6. Snow Water Lake is situated in the NE. corner of the Township.