

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 34 N., R. 63 E., MDM, NEVADA

CHAINS		
80.18	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a squared wooden post, 2x2x24 ins., with illegible scribe marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R63E R64E S 1 S 6 S 12 S 7</p> </div> <p>1975</p> <p>deposit the original wooden post alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>	
	<p>N. 1° 36' E., bet. secs. 1 and 6.</p> <p>Over nearly level land, through greasewood.</p> <p>24.00 Trail road, bears S. 62° E. and N. 62° W.</p> <p>24.80 Telephone lines, bear S. 62° E. and N. 62° W.</p> <p>25.60 Western Pacific Railroad track, bears S. 62° E. and N. 62° W.</p> <p>25.70 Trail road, bears S. 62° E. and N. 62° W.</p> <p>40.15 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R63E R64E ¼ S 1 S 6</p> </div> <p>1975</p> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>	
64.90	Trail road, bears ENE. and WSW.	
80.30	<p>Point for the cor. of Tps. 34 and 35 N., Rs. 63 and 64 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	