

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 34 N., R. 63 E., MDM, NEVADA

CHAINS		
	WEST, bet. secs. 30 and 31.	
	Over nearly level land, through greasewood.	
7.20	Fence, bears SE. and NW.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T34N R63E <math>\frac{1}{4}</math> <u>S 30</u> S 31</p>	
	1975	
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.	
79.54	Point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., at record bearing and distance, from the cor. of secs. 29, 30, 31 and 32; there is no remaining evidence of the original corner. This corner now refers to the cor. of secs. 30 and 31, T. 34 N., R. 63 E., only.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;"> T34N  R63E  S 30  S 31</p>	
	1975	
	raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.	
	<hr/>	
	From the cor. of secs. 29, 30, 31 and 32.	
	N. $0^{\circ} 59'$ E., bet. secs. 29 and 30.	
	Ascend 10 ft. over small embankment, slopes S.	
3.50	Edge of escarpment, bears E. and W., continue over nearly level land.	
39.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	