

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 33 N., R. 64 E., MDM, NEVADA

CHAINS

40.07

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T33N R64E \\ \frac{1}{4} \frac{S 32}{S 5} \\ T32N \end{array}$$

1975

raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

80.14

The cor. of secs. 5, 6, 31 and 32, monumented with a quartzite stone, 18x8x3 ins., mkd. with 1 groove on W. face and 5 grooves on E. face, firmly set and exposed 12 ins. above ground. (Record calls for a squared wooden post.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T33N R64E \\ \frac{S 31 | S 32}{S 6 | S 5} \\ T32N \end{array}$$

1975

deposit the original cornerstone and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post.

N. $89^{\circ} 07'$ W., bet. secs. 6 and 31.

Ascend 350 ft. over broken ENE. slope, through sagebrush, shadscale and scattering juniper.

40.05

Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base to top, with brass cap mkd.

$$\begin{array}{r} T33N R64E \\ \frac{1}{4} \frac{S 31}{S 6} \\ T32N \end{array}$$

1975