

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 64 E., MDM, NEVADA

CHAINS		
80.08	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R64E $\frac{S \ 2 \ \ S \ 1}{S \ 11 \ \ S \ 12}$</p> <p>1975</p> </div> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>	
20.72	<p>From the SE. cor. of sec. 1, on the E. bdy. of the Tp. S. 89° 13' W., along the S. bdy. of sec. 1. Over nearly level land, through greasewood.</p> <p>Intersect the W. bdy. of sec. 7, T. 34 N., R. 65 E. Point for the crossing closing cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>CC $\frac{T34N \ }{R64E \ }{S \ 12 \ }$</p> <p>1975</p> </div> <p>raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the NW. cor. of sec. 7, T. 34 N., R. 65 E., as reestablished by Potter, monumented with an iron post, 3 ins. diam., firmly set and exposed 7 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., surveyed concurrently under this same group, bears N. 0° 01' E., 12.87 chs. dist.</p>	
40.18	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R64E $\frac{S \ 1}{\frac{1}{4} \ S \ 12}$</p> <p>1975</p> </div> <p>raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p>	
80.36	<p>The cor. of secs. 1, 2, 11 and 12.</p>	