

RETRACEMENT AND PARTIAL RESURVEY, WEST BOUNDARY,  
T. 34 N., R. 65 E., MDM, NEVADA

## CHAINS

T34N  
R64E R65E  
| ¼  
| S 7  
|

1975

raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.

N. 0° 01' E., beginning new measurement.

27.14 The crossing closing cor. of sec. 12, T. 34 N., R. 64 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 64 E., surveyed concurrently under this same group.

40.01 The cor. of secs. 1, 6, 7 and 12, as reestablished by Potter, monumented with an iron post, 3 ins. diam., firmly set and exposed 7 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., executed under Group No. 26. This corner now refers to sec. 7 only and the brass cap is remarked.

R64E  
S 1 | T34N  
| R65E  
| S 7  
|

1975

raise a mound of stone, 2 ft. base, 2 ft. high, SE. of cor.

N. 0° 01' E., on the W. bdy. of sec. 6.

Over nearly level land, through greasewood.

19.70 Trail road, bears SE. and NW.

40.00 The ¼ sec. cor. of secs. 1 and 6, as reestablished by Potter, monumented with an iron post, 1 in. diam., firmly set and exposed 11 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., executed under Group No. 26. The brass cap is remarked AM 1975.

N. 0° 01' E., beginning new measurement.

39.98 The cor. of Tps. 34 and 35 N., Rs. 64 and 65 E., as reestablished by Potter, monumented with an iron post, 3 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 35 N., R. 65 E., executed under Group No. 26. This corner now refers to sec. 31, T. 35 N., R. 65 E., only and the brass cap is remarked.