

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 34 N., R. 65 E., MDM, NEVADA

## CHAINS

N. 0° 03' W., bet. secs. 5 and 6.

Over nearly level land, through greasewood.

- 39.96 The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., executed under Group No. 26. The brass cap is remarked.

T34N R65E

$\frac{1}{4}$   
S 6 | S 5

1975

N. 0° 02' W., beginning new measurement.

- 39.94 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.

From the cor. of secs. 17, 18, 19 and 20.

N. 89° 45' W., bet. secs. 18 and 19.

Over nearly level land, through greasewood.

- 39.96 The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 34 N., R. 65 E., executed under Group No. 26. The brass cap is remarked.

T34N R65E

$\frac{1}{4}$  S 18  
S 19

1975

N. 89° 54' W., beginning new measurement.

- 14.40 Intersect the E. bdy. of T. 34 N., R. 64 E.

Point for the closing corner of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N  
R64E R65E  
S 13 | S 18  
S 19 CC

1975

raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.