

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 33 E., MDM, NEVADA

CHAINS	Spur, slopes SW.; asc. 280 ft. over a broken SW. slope.
58.00	The cor. of secs. 1, 2, 11 and 12, monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner.
84.98	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R33E S 2 S 1 S 11 S 12</p>
	1976
	N. 0° 12' W., bet. secs. 1 and 2.
	Over mountainous land, through sagebrush and scattered juniper; asc. 280 ft. over a broken SW. slope.
12.00	Spur, slopes WNW.; desc. 680 ft. over a broken N. slope.
37.27	<p>The ¼ sec. cor. of secs. 1 and 2, monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T29N R33E ¼ S 2 S 1</p>
	1976
	N. 0° 48' W., beginning new measurement.
	Over mountainous land; desc. 360 ft. over a N. slope.
15.00	Wash in Rocky Canyon, 30 lks. wide, 2 ft. deep, course W.; asc. 440 ft. over a S. slope.
40.82	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to top, mkd. as described in the field notes of T. 30 N., R. 33 E., resurveyed concurrently under this same group.</p>